


EN166M-120-360/365/370/375/380W







High Efficiency PERC Monocrystalline Solar Module 120 Half-Cell Series

ABOUT ECONESS ENERGY

Established in 2009 by Jiangsu Huadong Group (founded in 1997), Econess Energy is a professional solution provider for solar energy. With current annual production capacity of 600 MW PERC polycrystalline cells and 3GW modules, Econess Energy now distributes its PV products to over 36 countries. As a strong, bankable partner, we are committed to building strategic, mutually beneficial collaboration with installers and developers.



KEY FEATURES

-  **Maximize limited space**
Half cell technology (low RS) combine with PERC, more internal reflection, maximum power output 380w
-  **Significantly reduce the hot spot effect**
Unique circuit design significantly reduces hot spot temperature and power loss
-  **IP68 junction box**
The highest waterproof level
-  **Excellent Anti-PID performance**
2 times of industry standard Anti-PID test by TUV
-  **Lower temperature coefficients**
Enhance power generation
-  **Certified to withstand the most challenging environmental conditions**
2400 Pa wind load · 5400 Pa snow load · 25mm hail stones at 82 km/h

SYSTEM & PRODUCT CERTIFICATES

- IEC 61215 / IEC 61730
- IEC 61701 / IEC 62804
- ISO 9001 : 2015 Quality Management System
- ISO 14001 : 2015 Environment Mangement System
- ISO 45001 : 2018 Occupational Health and Safety Management System




QUALITY WARRANTY

Econess Energy guarantees that defects will not appear in materials and workmanship defined by IEC61215 or IEC61730 under normal installation, use and maintenance as specified in Econess Energy's installation manual for 12 years from the warranty starting date.

PERFORMANCE WARRANTY

Monocrystalline Solar Module



ELECTRICAL PARAMETERS

Performance at STC (Power Tolerance 0 - +3%)

Maximum Power(Pmax/W)	360	365	370	375	380
Operating Voltage (Vmpp/V)	36.52	36.80	37.07	37.35	37.68
Operating Current(Imp/A)	9.86	9.92	9.99	10.05	10.10
Open-Circuit Voltage (Voc/V)	42.04	42.18	42.33	42.48	42.62
Short-Circuit Current(Isc/A)	10.40	10.47	10.53	10.60	10.67
Module Efficiency ηm (%)	19.76	20.04	20.31	20.59	20.86

Performance at NMOT


Maximum Power(Pmax/W)	266	270	274	278	282
Operating Voltage (Vmpp/V)	34.60	34.96	35.31	35.65	36.04
Operating Current(Imp/A)	7.79	7.83	7.87	7.91	7.95
Open-Circuit Voltage (Voc/V)	38.37	38.52	38.63	38.79	38.90
Short-Circuit Current(Isc/A)	8.31	8.36	8.41	8.46	8.51

STC: Irradiance 1000W/m², Cell Temperature 25°C, Air Mass AM1.5 NMOT: Irradiance at 800W/m², Ambient Temperature 20°C, Wind Speed 1m/s

MECHANICAL SPECIFICATION

Cell Arrangement	120 [2 x (10 x 6)]
Weight	20.0 kg (44.09 lb)
Module Dimensions	1755 x 1038 x 35mm(69.09 x 40.87 x 1.38 inch)
Cable Length	300 mm (11.81 inch)
Cable Cross Section Size	4mm ² (0.006 sq.in)
Front Glass	3.2 mm High Transmission, Tempered Glass
No.of Bypass Diodes	3/6
Packing Configuration (1)	31pcs/Pallet, 806pcs/40hq
Packing Configuration (2)	31pcs+4pcs/Pallet, 858pcs/40hq
Frame	Anodized Aluminium Alloy
Junction Box	IP68

I-V CURVE




OPERATING CONDITIONS

Maximum System Voltage	1000V (IEC) DC / 1500V (IEC) DC
Operating Temp	-40°C ~ +85°C
Maximum Series Fuse	20 A
Static Loading	5400 Pa
Conductivity at Ground	≤ 0.1Ω
Safety Class	II
Resistance	≥ 100MΩ
Connector	MC4 Compatible

TEMPERATURE COEFFICIENT

Temperature Coefficient(Pmax)	-0.34%/°C
Temperature Coefficient(Voc)	-0.27%/°C
Temperature Coefficient(Isc)	+0.035%/°C
NMOT	45±2°C

TECHNICAL DRAWINGS (mm)



Econess Energy Co., Ltd.

Am Seestern 8, 40547 Duesseldorf, Germany (Everwind GmbH) T +49 211 1576 3022 sales@everwind.de www.everwind.de

* This is preliminary datasheet and for reference only. The specifications and key features contained in this datasheet may deviate slightly from our actual products due to the on-going innovation and product enhancement. Econess Energy reserves the right to make necessary adjustment to the information described herein at any time without further notice.